



NEW

ROTO KOMPAKT

WITH ROTARY HEAT EXCHANGER

LOT6



2018

ec



technology

THE NEW ROTO K SERIES

THE ROTO K SERIES

Was completely redesigned and fulfills all the requirements of ErP 2018.

The air handling unit is equipped with a very efficient regenerative rotary heat exchanger. The rotor support structure has been optimized so that the rotor almost completely fills the housing cross-section. Lower pressure losses and higher recovery efficiencies are the positive consequences.

Rotary heat exchangers do not tend to freeze even at lower temperatures, consequently they still have the full heat recovery even at temperatures of -15°C or lower, and thus have a better annual utilization ratio in cold regions than efficient countercrossflow heat exchangers.

Furthermore, a part of the moisture is transferred from the extract air into the supply air so that the room air moisture does not decrease like in case of countercrossflow heat exchangers, thus, auxiliary humidification is usually not any more needed.

The double-wall housing was designed in such a manner, that a minimal use of sealing ensures maximum tightness.

- Heat recovery up to 80%
- Very low external leakage: L2 (DIN EN 1886)
- Double-walled housing with 40mm mineral wool (ROTO K...V)
- Double-walled housing with 50mm mineral wool (ROTO K...H)
- Very compact design




Image 1: Heat transfer rotary heat exchanger

THE TYPES

ROTO KOMPAKT V



This series comprises 4 sizes with an air flow of 770 m³/h up to 4.340 m³/h - nominal volume flow (ErP 2018).

With vertical air guidance and a small footprint the units can be accommodated in a space-saving way. The ideal solution for small installation rooms. The sized access doors allow unrestricted access to every installation part.

ROTO KOMPAKT H



This series, with horizontal air connections, comprises 6 sizes with an air flow of 857 m³/h up to 10.526 m³/h - nominal volume flow (ErP 2018).

CONTROLS

The devices are standard equipped with microprocessor controls, factory wired and tested. All sizes have constant volume fan operation. The desired air volumes can be easily entered into the remote control unit. Furthermore, an automatic mass flow correction is integrated in the controls. This means that even in winter only the desired air volume flow rates are fed into the building. These ventilation units therefore offer additional energy savings of up to 15%. Further control options such as CO₂, humidity or external volume flow control as well as an integrated Modbus-RTU interface ensure flexible application possibilities.

A WELL ROUNDED CONCEPT

HEAT RECOVERY:

The regenerative rotary heat exchanger of the ROTO K series achieves high efficiency rates up to 80 % throughout the year. The regenerative heat exchanger is made of corrosion-resistant aluminium and needs no frost protection.

HUMIDITY RECOVERY:

Up to 60% of the room humidity will be recovered by the regenerative heat exchanger. This avoids too dry room air and improves the comfort in the building.

ENERGY EFFICIENCY:

The high efficiency EC fans achieve a total efficiency of more than 60% and are therefore well above the efficiency class IE4.

The demand-controlled operation lead to optimized energy consumption by the continuous regulation of EC fans and control with external sensors.






Image 1: ROTO Kompakt V



Image 2: ROTO Kompakt H

AIR PERFORMANCE CURVES



OUR PRODUCT RANGE

IN LINE TUBE FANS

ETALINE and ETAMASTER, the No. 1 in saving energy.




DUCT FANS

Backward curved centrifugal fans, sound insulated, compact diagonal fans.



EXHAUST FANS

For industrial or kitchen exhaust, up to 120 °C.



ROOF FANS

With horizontal and vertical discharge, up to 120 °C.



COMPACT AHU

With counter flow heat exchanger with more than 90% heat recovery efficiency and EC fans. Available with horizontal or vertical air guidance respectively flat units for suspended ceiling mounting.



COMPACT AHU

With rotary heat exchanger with up to 80% heat recovery efficiency and EC fans. Available with horizontal or vertical air guidance.



ruck Ventilatoren GmbH

Max-Planck-Str. 5
D-97944 Boxberg

Tel. +49 (0)7930 9211-300
Fax +49 (0)7930 9211-166

www.ruck.eu
info@ruck.eu

